

LESSLEY
Strand Orientation Alignment In
Strand Coating Systems And Methods"
Atty. Docket No. 14120

Appl. No. 10/623,294
Confirm. No. 4116
Examiner B. Lamb
Art Unit 1762

Claims 1-13 (Canceled).

14 (Currently Amended). A strand coating system, comprising:
an adhesive dispensing device having an adhesive dispensing
orifice;

a strand guide member, the strand guide member includes a
strand guide not aligned with the adhesive dispensing orifice and the strand
axial orientation aligning member;

a strand axial orientation aligning member coupled to the
adhesive dispensing device,

the strand axial orientation aligning member positioned in
substantial alignment with the adhesive dispensing orifice, the strand axial
orientation aligning member disposed between the strand guide member and
the adhesive dispensing orifice,

the strand axial orientation aligning member is a pin having an
axis extending substantially transverse to an axis along which strand is drawn
past the adhesive dispensing device,

the strand axial orientation aligning member is a pin having a
recessed side portion.

Claim 15 (Canceled).

Claim 16 (Canceled).

LESSLEY
Strand Orientation Alignment In
Strand Coating Systems And Methods"
Atty. Docket No. 14120

Appl. No. 10/623,294
Confirm. No. 4116
Examiner B. Lamb
Art Unit 1762

17. (Currently Amended) The strand coating system of Claim 14 [34], the strand axial orientation aligning member is a pin having an axis extending substantially parallel to a direction in which adhesive is dispensed from the adhesive dispensing orifice.

18. (Previously Presented) The strand coating system of Claim 14, the strand guide member is coupled to a module.

19. (Previously Presented) The strand coating system of Claim 18, the strand guide member is a strand guide roller adjustably coupled to the module.

Claims 20-21 (Canceled).

22. (Previously Presented) A strand coating apparatus, comprising:

a module;

a fluid dispensing device having a fluid dispensing orifice, the fluid dispensing device coupled to an end of the module;

a plate coupled to a bottom of the module and extending beyond the end of the module to which the fluid dispensing device is coupled, the plate having an opening aligned with the fluid dispensing orifice,

a strand orienting pin protruding from a side of the plate opposite from a side of the plate on which the fluid dispensing device is located.

LESSLEY
Strand Orientation Alignment In
Strand Coating Systems And Methods"
Atty. Docket No. 14120

Appl. No. 10/623,294
Confirm. No. 4116
Examiner B. Lamb
Art Unit 1762

23. (Previously Presented) The apparatus of Claim 22,
a strand guide member coupled to the module;
the strand orienting pin located substantially between the strand
guide member and the fluid dispensing orifice, the strand orienting pin offset
relative to a path between the fluid dispensing orifice and the strand guide
member.

24. (Previously Presented) The apparatus of Claim 23, the strand
guide member includes a strand guide groove, the strand orienting pin offset
relative to a path between the fluid dispensing orifice and the strand guide
groove.

25. (Previously Presented) The apparatus of Claim 24, the fluid
dispensing device is an adhesive dispensing device having an adhesive
dispensing orifice.

26. (Previously Presented) The system of Claim 22, the strand
orienting pin having an axial dimension substantially parallel to a direction of
the fluid dispensing orifice, the strand orienting pin having a recessed side
portion.

27. (Previously Presented) A system for applying coating
materials onto a strand, the system comprising:

LESSLEY
Strand Orientation Alignment In
Strand Coating Systems And Methods"
Atty. Docket No. 14120

Appl. No. 10/623,294
Confirm. No. 4116
Examiner B. Lamb
Art Unit 1762

a fluid dispensing device having a fluid dispensing orifice from which fluid is dispensed,

a strand guide member coupled to the fluid dispensing device, the strand guide for guiding a strand drawn past fluid dispensing orifice;

a strand orienting pin located between the strand guide member and the fluid dispensing orifice so that a strand drawn from the strand guide member over the fluid dispensing orifice is engaged with the strand orienting pin,

a module,

a plate mounted on a bottom portion of the module and extending beyond an end portion of the module to which the fluid dispensing device is coupled, the plate having an opening aligned with the fluid dispensing orifice.

Claim 28 (Canceled).

29. (Previously Presented) The system of Claim 27, the strand orienting pin protruding from a side of the plate opposite from a side of the plate on which the fluid dispensing device is located.

30. (Previously Presented) The system of Claim 29, the strand guide member is a roller including a strand guide groove, the strand orienting pin offset relative to a path between the fluid dispensing orifice and the strand guide groove.

LESSLEY
Strand Orientation Alignment In
Strand Coating Systems And Methods"
Atty. Docket No. 14120

Appl. No. 10/623,294
Confirm. No. 4116
Examiner B. Lamb
Art Unit 1762

31. (Previously Presented) The system of Claim 27, the fluid dispensing device is an adhesive dispensing device.

Claim 32 (Canceled).

Claim 33 (Canceled).

34. (Previously Presented) A system for applying coating materials onto a strand, the system comprising:

an fluid dispensing device having a fluid dispensing orifice from which fluid is dispensed,

a strand guide member coupled to the fluid dispensing device, the strand guide for guiding a strand drawn past fluid dispensing orifice;

a strand orienting pin located between the strand guide member and the fluid dispensing orifice so that a strand drawn from the strand guide member over the fluid dispensing orifice is engaged with the strand orienting pin,

the strand orienting pin having an axial portion substantially parallel to a direction of the fluid dispensing orifice,

the axial portion having a recessed side portion within which a strand is captured when the strand is engaged with the strand orienting pin.